



ISO30 DIN69871 cone  
Taper 7/24

Teknomotor pull-stud

Power connector	
1	U
2	V
3	W
GND	Ground
A	Fan (L) 220V
B	Thermal protection
C	Thermal protection
D	Fan (N) 220V

Signal connector	
1	S1
2	S2
3	S3 tacho
4	not used
5	S5
6	0 V
7	+24V DC

Power S1/S6 60%[kW]	Base speed [rpm]	Base voltage [V]	Base frequency [Hz]
5.5/6.6	12000	380V	200
Min speed [rpm]	Max speed [rpm]	Absorb. [A]	Customer part number
2000	24000	11.4/13.4	ATC71002
grado di equilibratura: 2.5 norma ISO 1940			peso / weight 24.80 kg
Tolleranze non quotate: ±0.5mm Smussi non quotati: ±0.5mm		$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$
revisione n°	motivo di revisione		
0	Prima emissione		
dis. da / drawn Ing. Bottarel	appr. da / approved Ing. Perli	data / date 02/04/2013	sostituisce il sostituito dal
percorso / path			

# TEKNOMOTOR

Teknomotor S.r.l.  
Via Argenege 19, I-32030 Quero (BL)  
www.teknomotor.com

titolo/title  
ATC71-B-ISO30-SN

Cliente/Customer  
Catalogo

codice / drawing code  
1TC000-002

disegno n° / drawing n°  
1674

foglio / sheet  
1 / 1

scala  
1:2

 A4